

## IP camera

- Cameras of different brands and models That supports RTSP can be integrated in to the system
- Compatibility: SYSGuard3001 and SYSGuard6001

Product No:SYSGAC03

## Magnetic Contact

- Real time recognition of entry
- Max. distance from main unit: 200m
- Compatibility: SYSGuard 3001, SYSGuard 2001, SYSGuard 6001 (can be connected by using, SYSGuard6088 or SYSGuard 6081 Dry Contact Module)

Product No: SYSGAC05

## Vibration Sensor

- Real-time recognition of vibration
- Max. distance from main unit: 200m
- Compatibility: SYSGuard 3001, SYSGuard 2001, SYSGuard 6001 (can be connected by using, SYSGuard6088 or SYSGuard 6081 Dry Contact Module)

Product No: SYSGAC07

## Proximity Card

- Card for proximity readers
- Compatibility: SYSGAC08

Product No: SYSGAC09

## Signal Tower

- Warns users via sound and light during alarms
- Max. distance from main unit: 200m
- Compatibility: SYSGuard 6100

Product No: SYSGAC13

## Siren

- Warns users via sound during alarms
- Max. distance from connected module: 5m
- Compatibility: SYSGuard 6100

Product No: SYSGAC14

## Smoke Detector

- Real-time recognition of smoke
- Max. distance from main unit: 200m
- Compatibility: SYSGuard3001SYSGuard2001, SYSGuard 6001 (can be connected by using, SYSGuard6088 or SYSGuard 6081 Dry Contact Module)

Product No: SYSGAC04

## PIR Detector (Motion Detector)

- Real-time recognition of movement
- Max. distance from main unit: 200m
- Compatibility: SYSGuard3001, SYSGuard2001, SYSGuard 6001 (can be connected by using, SYSGuard6088 or SYSGuard 6081 Dry Contact Module)

Product No: SYSGAC06

## Proximity Reader

- Allows door access by reading proximity cards
- Max. distance from main unit: 200m
- Compatibility: SYSGuard 6200

Product No: SYSGAC08

## Power Adapter

- Main unit power adaptor
- 220 VAC input
- 12VDC output
- 2.5 A
- Compatibility: SYSGuard3001, SYSGuard6001 and SYSGuard2001

Product No: SYSGAC12



# SYSGUARD SENSOR LIST

For more information please call  
us or visit our website at  
**[www.exagate.com](http://www.exagate.com)**

HEADQUARTERS  
Sehit Ahmet Sk. No: 12/1 Mecidiyekoy/Istanbul/Turkey  
PO Box 34387  
Ph +90 0212 275 73 22 Fx +90 0212 275 73 66  
[info@exagate.com](mailto:info@exagate.com)

MARKETING & SALES SUPPORT  
[sales@exagate.com](mailto:sales@exagate.com)

TECHNICAL SUPPORT  
[support@exagate.com](mailto:support@exagate.com)

**SYSGuard 2010 Temperature & Humidity Sensor (High Sensitivity Series)**

- Real-time temperature sensor
- Temperature Range: -25 C° - 75 C°
- Temperature Tolerance: +/- 0,5 C°
- Temperature Resolution: 0,5 C°
- Max. distance from main unit: 200m
- Compatibility: SYSGuard2001

Product No: SYSG2010

**SYSGuard 2020 Temperature Sensor (Standard Series)**

- Real-time temperature sensor
- Temperature Range: -25 C° - 75 C°
- Temperature Tolerance: +/- 0,5 C°
- Temperature Resolution: 0,5 C°
- Max. distance from main unit: 200m
- Compatibility: SYSGuard2001

Product No: SYSG2020

**SYSGuard 2030 Air Flow Sensor**

- Real-time air flow recognition
- Measures the air current near air ducts, door-window entrances or ventilation
- Max. distance from main unit: 200m
- Compatibility: SYSGuard2001

Product No: SYSG2030

**SYSGuard 6010 Temperature & Humidity Sensor (High Sensitivity Series)**

- Real-time temperature & humidity sensor
- Temperature Range: -25 C° - 70 C°
- Temperature Tolerance: +/- 0,4 C°
- Temperature Resolution: 0,1 C°
- Relative Humidity Range: %0 Rh - %90 Rh
- Relative Humidity Tolerance: +/- %3 Rh
- Relative Humidity Resolution: %0,1 Rh
- Max. distance from main unit: 200m
- Compatibility: SYSGuard3001 and SYSGuard6001

Product No: SYSG6010

**SYSGuard 6011 Temperature & Humidity Sensor (Standard Series)**

- Real-time temperature & humidity sensor
- Temperature Range: -25 C° - 70 C°
- Temperature Tolerance: +/- 0,5 C°
- Temperature Resolution: 0,1 C°
- Relative Humidity Range: %0 Rh - %90 Rh
- Relative Humidity Tolerance: +/- %4,5 Rh
- Relative Humidity Resolution: %0,1 Rh
- Max. distance from main unit: 200m
- Compatibility: SYSGuard3001 and SYSGuard6001

Product No: SYSG6011

**SYSGuard 6020 Temperature Sensor (High Sensitivity Seri)**

- Real-time temperature sensor
- Temperature Range: -25 C° - 75 C°
- Temperature Tolerance: +/- 0,5 C°
- Temperature Resolution: 0,1 C°
- Max. distance from main unit: 200m
- Compatibility: SYSGuard3001 and SYSGuard6001

Product No: SYSG6031

**SYSGuard 6021 Temperature Sensor (Standard Series)**

- Real-time temperature sensor
- Temperature Range: -25 C° - 75 C°
- Temperature Tolerance: +/- 0,5 C°
- Temperature Resolution: 0,5 C°
- Max. distance from main unit: 200m
- Compatibility: SYSGuard3001 and SYSGuard6001

Product No: SYSG6021

**SYSGuard 6030 Flood Sensor**

- Real-time recognition of liquid/flood
- Max. distance from main unit: 200m
- Compatibility: SYSGuard3001 and SYSGuard6001

Product No: SYSG6030

**SYSGuard 6031 Water Detect Cable**

- Real-time recognition of liquid/flood
- Cable length: 1m
- Can only work connected to SYSGuard6030, SYSGuard6200 and SYSGuard3001

Product No: SYSG6031

**SYSGuard 6035 Water Detect Cable**

- Real-time recognition of liquid/flood
- Cable length: 5m
- Can only work connected to SYSGuard6030, SYSGuard 6200 and SYSGuard3001

Product No: SYSG6035

**SYSGuard 6040 Triphase VF Module**

- Real-time threephase voltage & frequency module
- Max. distance from main unit: 200m
- Compatibility: SYSGuard3001 and SYSGuard6001

Product No: SYSG6040

**SYSGuard 6043 Triphase Energy Module**

- Real-time threephase voltage, current, frequency, power, active, reactive, capacitive and Cos Fi module
- Max. distance from main unit: 200m
- Compatibility: SYSGuard6001

Product No: SYSG6043

**SYSGuard 6050 RS-232 Module**

- Integration module for UPS
- Max. distance from main unit: 200m
- Compatibility: SYSGuard6001

Product No: SYSG6050

**SYSGuard 6060 LCD Module**

- Show sensor information on screen
- 4\*20 character
- Buzzer
- Max. distance from main unit: 200m
- Compatibility: SYSGuard3001 and SYSGuard6001

Product No: SYSG6060

**SYSGuard 6070 Expansion Module**

- Increases the number of sensors that Can be added to the main unit
- 8 ExaBus ports
- Max. distance from main unit: 200m
- Compatibility: SYSGuard6001

Product No: SYSG6070

**SYSGuard 6081 Dry Contact Module**

- 1 dry contact input
- Max. distance from main unit: 200m
- Compatibility: SYSGuard3001 and SYSGuard6001

Product No: SYSG6081

**SYSGuard 6088 Dry Contact Module**

- 8 dry contact input
- Max. distance from main unit: 200m
- Compatibility: SYSGuard3001 and SYSGuard6001

Product No: SYSG6088

**SYSGuard 6080 Dry Contact Module**

- 24 dry contact input
- Max. distance from main unit: 200m
- Compatibility: SYSGuard6001

Product No: SYSG6080

**SYSGuard 6094 Relay Output Module**

- 4 relay output
- 5A current per output
- Max. distance from main unit: 200m
- Compatibility: SYSGuard3001 and SYSGuard6001

Product No: SYSG6094

**SYSGuard 6090 Relay Output Module**

- 12 relay output
- 0,5A current per output
- Max. distance from main unit: 200m
- Compatibility: SYSGuard3001 and SYSGuard6001

Product No: SYSG6090

**SYSGuard 6100 Alarm Signal Input Module**

- Module that can be connected with signal tower or Siren
- Connectable devices: Signal tower, Siren
- Max. distance from main unit: 200m
- Compatibility: SYSGuard3001 and SYSGuard6001

Product No: SYSG6100

**SYSGuard 6120 Integration Module**

- Integration module for UPS, generator, air conditioner etc...
- Supports SNMP, RS-485, RS-232, ModBus protocols
- Max. distance from main unit: 200m
- Compatibility: SYSGuard6001

Product No: SYSG6120

**SYSGuard 6131 Analog Module**

- 1 analog port
- 4-20mA or 0-10V
- Max. distance from main unit: 200m
- Compatibility: SYSGuard3001 and SYSGuard6001

Product No: SYSG6131

**SYSGuard 6130 Analog Module**

- 24 analog ports
- Max. distance from main unit: 200m
- Compatibility: SYSGuard6001

Product No: SYSG6130

**SYSGuard 6160 Voice Calling Module**

- Send warnings via voice mail during alarms
- Max. distance from main unit: 200m
- Compatibility: SYSGuard3001 and SYSGuard6001

Product No: SYSG6160

**SYSGuard 6170 Air Flow Sensor**

- Real-time air flow recognition
- Measures the air current near air ducts, door-window entrances or ventilation
- Max. distance from main unit: 200m
- Compatibility: SYSGuard3001 and SYSGuard6001

Product No: SYSG6170

**SYSGuard 6180 Air Quality Sensor**

- Measure the air quality parameters
- Measured parameters: NH3,NOx, smoke, CO2
- Compatibility: SYSGuard3001 and SYSGuard6001

Product No: SYSG6180

**SYSGuard 6200 Combo Sensor**

- 1 Temperature & Humidity Sensor, 4 units Dry Contact Input, 2 units Relay Output, 1 unit Proximity Module Input port, 1 unit Water Detect Cable input port
- Max. distance from main unit: 200m
- Compatibility: SYSGuard3001 and SYSGuard6001

Product No: SYSG6200

**SYSGuard 6210 Battery Pack**

- Allows SYSGuard systems to work uninterrupted during blackout s
- 12V - 55W
- 12 hours backup
- Compatibility: SYSGuard3001 and SYSGuard6001

Product No: SYSG6210

**GSM Module**

- Send warnings via SMS during alarms
- Max. distance from main unit: 3m
- Compatibility: SYSGuard3001 and SYSGuard6001

Product No: SYSGAC01